

USB-2000-FLK-50

USB 2.0 Fiber Extender System
Up to 10km over Singlemode Fiber Optics



SUMMARY

- True plug and play support for USB 1.1 (low-speed, full-speed) and USB 2.0 highspeed devices operating up to 480Mb/s.
- Supports all major operating systems including Windows, MAC-OS, Linux and Sun.
- Four USB ports provided at device side remote extender (RX).
- Number of devices can be increased using standard USB hubs.
- Powered at both the local extender (TX) and remote extender (RX) modules.
- RX USB ports support high powered (500mA) devices.



SPECIFICATIONS

4-Port 10km Singlemode fiber Extender.
International 100-240V power adapters
USB cable 2m (6.6 ft)
TX connector (upstream) 1 x USB Type B
RX connector (downstream) 1 x Duplex LC
RX connector (upstream) 1 x Duplex LC
RX connector (downstream) 4 x USB Type A
Power adapter capacity 5V DC @ 3A (connected at TX and RX)
Power available to USB at REX 4 x 500mA
TX dimensions 107mm x 84mm x 34mm (4.25" x 3.4" x 1.4")
RX dimensions 114mm x 106mm x 38mm (4.5" x 4.2" x 1.5")
TX/RX weight 0.3 kg (0.6 lb)
Total system shipping weight 1.1 kg (2.4 lb)
Temperature range 4°C to 40°C
Regulatory Testing FCC, CE Class A

CONTACT

1-(800)-4TV-TEST (US and Canada)
1-(800) 488-8378
1-(516)-671-7278
FAX 1-(516)-671-3362