

FEATURES

- ▷ Genlock/Sync
- ▷ Remote camera and system power (optional)

APPLICATIONS

- ▷ Camera signal extender
- ▷ Studio link

An economic solution designed for fiber transmission



Transmit




Receive

The VB-3609 is part of the versatile LightBrix line of compact, rugged fiber transport products. Ideal for a box camera mounted to a robotic PTZ head, the VB-3609 will transport a full complement of camera signals, including 4K quad link, as well as an option to supply power to the transmitter and camera, via

a SMPTE hybrid cable. By utilizing the SMPTE cables fiber strands for signal transport and its copper wires for power, the transmitter unit, camera and PTZ head all receive power from the base unit. This allows for flexible setup, strike and mobility by having the entire camera position free of power outlets.

APPLICATION



TECHNICAL SPECIFICATIONS

Serial Data

Number of Channels	2
Type	RS232, RS422
Data Rate	DC – 1Mbps

Tally/GPIO

Number of GPI Inputs	1
Number of Tally Inputs	1
Number of GPI Outputs	1
Number of Tally Outputs	1
Inputs	Short to GND or TTL Low to Activate
Outputs	Relay Contact Closure (30V, 2A max)

Genlock/Sync

Number of Inputs	1
Number of Outputs	1
Type	Analog Black Burst (NTSC, PAL), HD Tri-Level

Optical

Operating Wavelengths	1471-1611nm
Tx Laser Output Power	0dBm (Class 1 Laser)
Receiver Sensitivity	-20dBm
Fiber Compatibility	Single-mode
Optical Connector Types	SC, ST, LC
Distance Limit	20km w/Single-mode and can be made as per

Overall

Dimensions	(LxWxH) 7.25"x5.75"x1.75"
------------	---------------------------

Power

Power Input:	2.5mm jack
Center Pin	+
Power Rating:	nominal15w max@12 VDC

Comp Vid

Number of Inputs	1
Number of Outputs	1
Type	NTSCL/PAL
Impedance	75SL

ORDERING INFORMATION

VB-3609 (HD video)

Part #	Description
VB-3609-XX-CA-8A-ST	Bidirectional Analog Composite Video Transceiver with 8 Bidirectional Audio, Genlock/Sync, 2 Serial Data, 1 Tally & GPIO, 1 Single-mode fiber, ST connector
VB-3609-XX-CB-8B-ST	Bidirectional Analog Composite Video Transceiver with 8 Bidirectional Audio, Genlock/Sync, 2 Serial Data, 1 Tally & GPIO, 1 Single-mode fiber, ST connector