

### FEATURES

- ▷ Excellent Value
- ▷ Compact Size
- ▷ Rugged Aluminum Enclosure
- ▷ Highest Quality Components

### APPLICATIONS

- ▷ Live Broadcast
- ▷ Arenas and Stadiums
- ▷ Shared Control Rooms
- ▷ Campus Facilities



MultiDyne's JUICE-48 and JUICE-60 are robust portable power supplies that allow users to send signals from the camera up to 300 meters without the need for local power or batteries.

Pairing any of the MultiDyne SilverBack camera-mounted transceiver products with a JUICE transmits any camera signal, including 12G-SDI video, audio, intercom, control data, GPIOs, tally, and power, making it the perfect solution for news, sports, ENG, D-SNG, OB, and multicamera studio applications.

- Provides power to SilverBack Fiber Camera Adapters over SMPTE Hybrid Fiber
- Uses only one single-mode fiber cable
- Send power up to 300 meters, without requiring local power or batteries at the camera
- Useful at golf courses, sports, and entertainment venues as well as multi-venue sporting events without a power infrastructure

### TECHNICAL SPECIFICATIONS

#### Electrical

	JUICE 48		JUICE 60	
Power Input, Voltage	90 - 264 VAC	127-370 VDC	90 - 264 VAC	127-370 VDC
Power Input, Frequency	47 - 63Hz		47 - 63Hz	
Power Output, DC Voltage	54 VDC		60 VDC	
Power Output, Current	2.7A		5.5A	
Rated Power (Convection)	180 W		300 W	

#### Mechanical, Environmental

Working Temperature	-30 - +55C (Refer to "Derating Curve")	-30 - +55C (Refer to "Derating Curve")
Working Humidity	20 - 90% RH non-condensing	20 - 90% RH non-condensing
Dimensions	10.5" x 5.74" x 3.45" (L x W x H)	12.75" x 5.74" x 3.45" (L x W x H)
Weight	4.4 lbs	6.2 lbs.

### ORDERING INFORMATION

Part #	Description
JUICE-48V-SPPST2F	Juice 48 External Power Supply, SMPTE-304M (wet) & 2 STs (dry); Delivers 48V to Camera
JUICE-60V-SPPST2F	Juice 60 External Power Supply, SMPTE-304M (wet) & 2 STs (dry); Delivers 60V to Camera

Please contact MultiDyne Sales for additional available connector configurations